

HÄFELE

FESTOOL
CONTURO
CREATE THE
PERFECT EDGE



SUPPLIED WITH:

Edging holder, additional roller, trimming machine, scraper, base runner scratch protector with 3 x felt pads, 5 x polishing felt, 20 x abrasive sheets StickFix Brilliant 2 80 x 133 mm P320, hand sanding block 80 x 133 mm, 5 x StickFix sanding cloth S 800, polish MPA 6000.

FESTOOL

FESTOOL CONTURO

KA 65 HAND HELD EDGE BANDER

Edging straight surfaces, curves, radii, convex and concave shapes as well as internal corners is easy with the CONTURO from FESTOOL. Edging can even be attached to mitred edges to an outstanding quality with the stationary unit. Quick, easy and clean – ideal for shaped parts and small batches. Suitable for machining all types of wood, plastic or melamine edging with a height of 18 – 65 mm and edge thickness of 0.5 – 3.0 mm (depending on material). The CONTURO is packed away safely in a SYSTAINER, extremely mobile and delivers a perfect edge quality, even in combination with system accessories.



Main Applications

- > Affixing wooden, plastic or laminated plastic edging to panel materials
- > Attach edging to simple rectangular components or more complex free forms
- > Suitable for mobile use, for rapidly reworking edges on site
- > Suitable for stationary use and small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°

Strengths And Benefits

- > Clean and efficient cartridge gluing system
- > Adhesive melts according to requirements and does not boil, discolour or deteriorate
- > Stationary application for greater versatility
- > Easy to handle, perfect ergonomics, clear view of the work piece
- > Nozzle system that is easy to clean, machine housing does not heat up, allowing safe working progress

Technical Data

- > Power: 1,200 W
- > Mains frequency: 50/60 Hz
- > Edging height: 18 – 65 mm
- > Edging thickness: 0.5 – 3.0 mm
- > Inner radius: > 50 mm
- > Heating time: approx. 8 min
- > Melting temperature default setting: Setting 1: 190° C/Setting 2: 200° C
- > Melting temperature setting range: Setting 1/2: 100 – 210° C
- > Feed speed 1st gear: 2 m/min
- > Feed speed 2nd gear: 4 m/min
- > Safety class: I
- > Weight (without glue cartridges & mains cable): 7.9 kg

ADHESIVE CARTRIDGE EVA - NATURAL ADHESIVE CARTRIDGE FOR CONTURO EDGE BANDER

EVA universal adhesive with high melting point, also suitable for use on objects with a higher resistance to temperatures. Natural colour tone suitable for all types of decor. Affixing wooden, plastic or laminated plastic edging to panel materials.



PERFECT WEIGHT DISTRIBUTION DUE TO TRANSVERSELY MOUNTED APPLICATION SYSTEM. CONTACT ROLLER FOR BETTER TRANSFER OF FORCE ALONG HANDLES. FIXED EDGE GUIDE TRANSMITS FORCE TO TOP OF WORK PIECE EDGE REGARDLESS OF THE EDGING HEIGHT, DIRECT VIEW OF THE CONTACT ROLLER.

	Cat. No.
KA 65 CONTURO Edge Bander Set	004.02.370
Adhesive Cartridge EVA - Natural (48 cartridges per carton)	004.02.371

Packing: 1 Piece

HÄFELE

FESTOOL

FESTOOL CONTURO - 01.2016

Häfele Australia Pty. Ltd. | 8 Monterey Road | Dandenong | Victoria 3175
Phone: 1300 659 728 | **Fax:** (03) 9212 2001 | **Email:** info@hafele.com.au | **www.hafele.com.au**

HÄFELE LOCATIONS:

Australia | MELBOURNE | SYDNEY | NEWCASTLE | BRISBANE | ADELAIDE | LAUNCESTON | HOBART | PERTH